

## BATTERY STRAPPING TOOL FOR PLASTIC STRAP WITH FRICTION WELD



### TECHNICAL SPECIFICATIONS

#### DIMENSIONS

<b>Lenght</b>	315 mm
<b>Width</b>	140 mm
<b>Height</b>	183 mm
<b>Weight</b>	4.1 Kgs

#### POWER SUPPLY

<b>Battery</b>	14.8V-3 A/h LI-PO
----------------	-------------------

#### PRESTAZIONI


<b>Tension max force</b>	1100N / 3500N
<b>Tensioning Speed</b>	12mt/m
<b>Sealing</b>	Friction Welding
<b>Joint Strength</b>	75% of breaking strenght*

\* variable according to strap type

### MODELS

CODE	TYPE	STRAP	THICKNESS
T209997	ITI20 / 13 mm-16 mm With one battery	PP-PET	0.5 mm - 1.05 mm
		13 mm-16 mm	
T2099971	ITI20 / 13 mm-16 mm With one battery + battery charger	PP-PET	0.5 mm - 1.05 mm
		13 mm-16 mm	
T2099972	ITI20 / 13 mm-16 mm With two batteries + battery charger	PP-PET	0.5 mm - 1.05 mm
		13 mm-16 mm	

#### EMBOSSED POLYESTER STRAP



#### SMOOTH POLYESTER STRAP



#### POLYPROPYLENE STRAP



ITIPACK s.r.l.

Via Capovilla, 73/bis - 36030 - VILLAVERLA (Vicenza) Italy

Phone. +39 0445 855 977 r.a. - Fax +39 0445 350034

e-mail : info@itipack.it - Web: www.itipack.com